



## HM-200

RANGE	pH: 0.0~14.0pH
	EC: 0~9990 $\mu$ S/0~20mS
	TDS: 0~9990ppm
	Temp: 0.0~55°C/ 32~130°F
RESOLUTION	pH: 0.1pH
	EC: 0.1 $\mu$ S (0~99.9) 1 $\mu$ S (100~999) 10 $\mu$ S (1000~9990) 0.01mS (0.01~20.00)
	TDS: 0.1ppm (0~99.9) 1ppm (100~999) 10ppm (1000~9990)
	Temp: 0.1°C/°F
ACCURACY	pH: $\pm$ 0.1pH
	EC: $\pm$ 2%
	TDS: $\pm$ 2%
	Temp: $\pm$ 1°C / $\pm$ 1.8°F
CALIBRATION	Digital
POWER	2 x AA
SIZE	14 x 6.6 x 2.8 cm (5.5 x 2.6 x 1.1 in)
	WEIGHT



Removable cover



Portable



Backlit

## FEATURES

- pH / EC / TDS / temperature measurement
- 5 units: pH,  $\mu$ S, mS, ppm 0.5 (NaCl) Scale & 0.7 (442<sup>TM</sup>) Scale
- Automatic Temperature Compensation Function (ATC)
- Digital calibration
- Large readability LCD screen
- Simultaneous display of three measured values of  
pH / EC or TDS / temperature
- Replaceable sensors
- Included Accessories: Protective cover, 2 AA batteries,  
pH 4 & 7 calibration solution, pH preservation solution