



UbiBot GS1-AL4G1RS Industrial-Grade (WiFi / SIM) Temperature Humidity Light Data Logger IoT System

SKU: UBIGS1AL4G1RS
Manufacture Warranty period: 12 months
Country of Origin: China

Introduction

UbiBot® industrial-grade GS1-AL4G1RS is a cloud-based environmental monitoring data logger. It supports WiFi and mobile GPRS/3G/4G 2 types of connection. A mobile GPRS/3G/4G network provides internet connection when WiFi is not available. With its embedded temperature, humidity and ambient light sensors, it detects environmental data all day round and automatically syncs all data to the UbiBot® IoT cloud platform, allowing you to access data and monitor the environment remotely from anywhere in the world via the free UbiBot APP or Web Console and to receive real-time alerts.

GS1-AL4G1RS is IP65 dustproof and water-resistant for outdoor use.

It supports multiple 5V RS485 external probes, but only one of each type can be connected at a time.

The clear 4" LCD screen allows you to instantly view the latest data.

UBIBOT GS1-AL4G1RS unable to support DS18B20-Audio Temperature Probe.

Features

- Built-in temperature, humidity, and ambient light sensors.
- 2.4 GHz WiFi and mobile GPRS/3G/4G 2 types of connection, no need of hubs or gateways; a free UbiBot Global SIM Card is included.
- Industrial-grade shell, strong and durable; IP65 water-resistant for outdoor use.
- 4" high-quality LCD screen displaying current environmental conditions.
- Free App & Web Console to access and monitor real-time data remotely, no subscription fee.
- UbiBot cloud storage for historical data; free historical data export.
- Multiple ways of real-time alerts: App notifications, emails, phone calls, SMS, HTTP.
- Working with IFTTT, Google Sheet, Alexa.
- Supporting multiple RS485 external probes; only one of each type can be connected at a time; GS1-AL4G1RS-1DS also supports 1 x DS18B20-Audio Temperature Probe.
- Easy setup with free UbiBot App or PC tools.
- Memory with a capacity of 300,000 records stores all data even if the network is temporarily disconnected, which ensures there are no gaps in the data history.

- Three types of power supply: internal lithium battery, Type-C 5V (USB cable provided), and DC 12V (not included).
- Compliance with CE, EN 12830, FCC, FDA CFR21, IC, RCM, RoHS, TELEC.

Note:

- For WiFi connection, GS1-AL4G1RS can only work with a 2.4 GHz WiFi network.
- **5 GHz WiFi is not supported.**
- It supports multiple RS485 external probes, but only one of each type can be connected at a time.
- GS1-AL4G1RS is IP 65 waterproof, but not resistant to high humidity over 90%.

Application

- Online real-time detecting temperature, humidity and light level
- Agriculture
- Greenhouse
- Museum
- Wine Cellar
- Pharmacy
- Horticulture
- Animal Breeding Warehouse

Package includes

1 x GS1-AL4G1RS device
1 x manual book
1 x Type-C USB cable (1m)
1 x Singapore Safety Mark 5V/2A Power Adapter



- Data sync via WiFi & SIM connectivity
- 24/7 temperature & humidity monitoring
- Waterproof, durable in extremely humid environments
- Multiple power supply methods
- Larger internal storage with up to 300,000 records
- No hub required

Specifications

Temperature	
Range:	-20°C to 60°C (-4°F to 140°F)
Typical Accuracy:	±0.3°C
Humidity	
Range:	10% to 90%, No condensation
Typical Accuracy:	±3%RH
Ambient Light	
Range:	0 to 83,000 lux
Typical Accuracy:	±2%
External Probe Connector	
Black connector for 5V RS485 Probe	
Operation System:	iOS 11+, Android 8.1+, or Windows 7+, or masOS v10.8+
Memory:	300,000 sensor records
WiFi Information:	supports 20MHz or "Auto" setting supports OPEN, WEP, or WPA/WPA2 types, WPA2-Enterprise (802.1x / RADIUS authentication) network is not supported, requires 2.4GHz (802.11 b/g/n), channels 1-13 (5GHz WiFi NOT supported)
Mobile Networks (Supports GPRS/3G/4G (micro SIM). SIM card is not provided)	
LTE FDD:	B1/B3/B5/B8
LTD TDD:	B34/B38/B39/B40/B41
WCDMA:	B1/B5/B8
GSM:	900/1800 MHz
Screen Size	4"
Colour	White
Material	Flame resistant ABS+PC
Switch Type	button
Power Source	Internal Lithium batteries, Type C USB, DC 5V-12V/2A charger
Battery Capacity	2900 mAh
Dimensions	11.5 x 9 x 5.5 cm
Weight	475g ± 3g

External Probes & Accessories



(Optional)

(With splitters, it supports multiple RS485 probes)

- TH30S-B Temperature and Humidity Probe.
- Soil Temperature and Moisture Sensor.
- PT 100 Industrial-grade Temperature Probe.
- Wind Speed Sensor.
- CO2 Probe.
- ONLY Model No. GS1-AL4G1RS-1DS supports 1 x DS18B20-Audio Temperature Probe.

NOTE:

- Only 1 RS485 probe can be connected at a time.
- For GS1-AL4G1RS-1DS, Wind Speed Sensor is incompatible with DS18B20-Audio Temperature Probe.



The cloud-based IoT platform

UbiBot® offers a revolutionary way to monitor environmental conditions where they matter. The sensors synchronize data to UbiBot® IoT Platform using WiFi, Cellular or Ethernet connection (depending on the specific model purchased). Users can then access data from anywhere via a smartphone or the Web console.

Features:

- **Data Management:** Manage all your IoT data in one place; you could add as many devices as you want to one UbiBot account.
- **Unlimited Storage:** Unlimited cloud-based storage ensures you will never run out of space. This allows you to view all your historical data via UbiBot App or Web.
- **Free App & Web Console:** Using UbiBot App and Web Console is free. Powerful and thoughtful features provide you brilliant experience.
- **Analysis and Visualization:** Use powerful analysis and visualization tools to get the most out of your data; spot trends and direct comparisons.
- **Real-Time Alerts:** Fully customizable alert system will notify you via App notifications, emails, phone call/SMS, HTTP whenever any metric goes out of the range preset.
- **Highly Secure Platform:** UbiBot IoT platform is designed to keep all your data secure so you never have to worry about hackers or other security issues.
- **Working with IFTTT, Alexa, Google Assistant, Google Sheet**
- Compliant with FDA CFR21

Details:

Real-time and history data

The UbiBot Platform is a cloud-based IoT platform where all measured data is uploaded and stored. UbiBot App and Web Console allow you to view current data as well as historical data in graphs.

Customizable alerts and bulk operation

Setting and receiving alerts on your devices helps you to get notified of the conditions timely. When you have many devices to manage, it's time-consuming to set each alert rule one by one. Therefore, we've developed a bulk operation module with which you can set the same rule for many devices at a time.

Data export

On UbiBot Platform, you can download the history data in CSV or PDF format. The CSV file only contains raw data, while the PDF file is a summarized report with average, maximum and minimum value within the chosen period. The PDF file is much easier to read and archive.

Device sharing and bulk operation

For business users, centralized control over multiple devices is available, with no limit on the number of devices in one account. Also available are bulk operations that apply to sensor settings, alerts, and remote control routines. Devices can be shared with other people, which allows for distributed management by different colleagues.

Intelligent automation in UbiBot platform

UbiBot is committed to building intelligent industrial and home ecosystems. By integrating temperature and humidity sensors and the smart plug SP1 in one system, automated operation is achieved through data linkage. For example, fans can be switched on when the temperature rises to 30 °C.


Data forwarding

UbiBot is an open platform that provides cloud-based services while supporting customers to use their own storage servers. With the data forwarding service, you can forward the data collected by your device to your own private URL to protect privacy.

Platform-based calibration

UbiBot platform supports data calibration both on the platform level as well as the device level. One-step calibration, instant display, no impact on historical data.

View Data from Mobile APP Dashboard



View Data from PC Dashboard

Channel ID	Channel Name	Device ID	Parameter	Temperature	Humidity	Light	PM2.5	PM10	CO2	TVOC	NO2	SO2	Current Voltage	Current Current	Current Power
C-54498	GMM Showroom-Printer	06100000000000000000	Printer	26.6	53.0	4.1	-45	109.1	629.6	30.2	0.0	0.0	4.1V	0.0A	0.0W
C-54499	GMM Showroom-WBIPms	06100000000000000000	WBIPms	26.6	53.0	4.1	-45	109.1	629.6	30.2	0.0	0.0	4.1V	0.0A	0.0W
C-54500	GMM Showroom-Printer	06100000000000000000	Printer	26.6	53.0	4.1	-45	109.1	629.6	30.2	0.0	0.0	4.1V	0.0A	0.0W
C-54501	GMM-C33 Controller	06100000000000000000	Controller	26.6	53.0	4.1	-45	109.1	629.6	30.2	0.0	0.0	4.1V	0.0A	0.0W
C-54498	06100000000000000000	Printer	Printer	26.6	53.0	4.1	-45	109.1	629.6	30.2	0.0	0.0	4.1V	0.0A	0.0W
C-54499	06100000000000000000	WBIPms	WBIPms	26.6	53.0	4.1	-45	109.1	629.6	30.2	0.0	0.0	4.1V	0.0A	0.0W
C-54500	06100000000000000000	Printer	Printer	26.6	53.0	4.1	-45	109.1	629.6	30.2	0.0	0.0	4.1V	0.0A	0.0W
C-54501	06100000000000000000	Controller	Controller	26.6	53.0	4.1	-45	109.1	629.6	30.2	0.0	0.0	4.1V	0.0A	0.0W
C-54502	06100000000000000000	Printer	Printer	26.6	53.0	4.1	-45	109.1	629.6	30.2	0.0	0.0	4.1V	0.0A	0.0W
C-54503	06100000000000000000	WBIPms	WBIPms	26.6	53.0	4.1	-45	109.1	629.6	30.2	0.0	0.0	4.1V	0.0A	0.0W
C-54504	06100000000000000000	Printer	Printer	26.6	53.0	4.1	-45	109.1	629.6	30.2	0.0	0.0	4.1V	0.0A	0.0W
C-54505	06100000000000000000	Controller	Controller	26.6	53.0	4.1	-45	109.1	629.6	30.2	0.0	0.0	4.1V	0.0A	0.0W
C-54506	06100000000000000000	Printer	Printer	26.6	53.0	4.1	-45	109.1	629.6	30.2	0.0	0.0	4.1V	0.0A	0.0W
C-54507	06100000000000000000	WBIPms	WBIPms	26.6	53.0	4.1	-45	109.1	629.6	30.2	0.0	0.0	4.1V	0.0A	0.0W
C-54508	06100000000000000000	Printer	Printer	26.6	53.0	4.1	-45	109.1	629.6	30.2	0.0	0.0	4.1V	0.0A	0.0W
C-54509	06100000000000000000	Controller	Controller	26.6	53.0	4.1	-45	109.1	629.6	30.2	0.0	0.0	4.1V	0.0A	0.0W
C-54510	06100000000000000000	Printer	Printer	26.6	53.0	4.1	-45	109.1	629.6	30.2	0.0	0.0	4.1V	0.0A	0.0W

Home
0.00 Credits
SIM Card
Messages
Spent
Printing
API Block
Blue
English
su2***@gmm.com.sg

C-54498
No description

26.6 53.0 4.1 -45 109.1 629.6 30.2

49.4

Show all sensors

Orders Bills Share Clear Channel Data Delete Device

Owner:	gmmtechnoworld	Access:	Private Space
Channel ID:	54498	Current Plan:	ubilog_free Change
Serial Number:	Q95G***1GS1 Copy	Used Space:	1.9 MB
Product ID:	ubilog-gs1-aeth1rs	Monthly Traffic Downloads:	118.8 KB
		Network:	MAC Address: fc:45:c3:b7:8e:7d Copy Wi-Fi: GMMTechnoworld

Private View
Rules
Trigger Logs
Settings
Pending Commands
Executed Commands
API Keys
Data Import/Export
Public View
Logs

Sample
From 28/11/2022 To 29/11/2022
Refresh
Download
Select sensor
Accessibility
Chart Extension

Temperature(°C) : 26.6°C

Humidity(%) : 53.0%


Voltage(V) : 4.1V

WIFI RSSI(dBm) : -45.0dBm



Download Data in Excel or PDF Format

created_at	field1 (Temperature °C)	field2 (Humidity)	field3(Light)	field4(Voltage)
2019-05-27T15:28:08+08:00	25.88121	60	81.639999	5
2019-05-27T15:28:10+08:00	25.894562	60	76.439995	5
2019-05-27T15:28:12+08:00	25.937286	61	76.919998	5
2019-05-27T15:28:14+08:00	25.937286	61	79.5	5
2019-05-27T15:28:15+08:00	25.96666	62	77.799995	5
2019-05-27T15:28:16+08:00	25.96666	62	75.919998	5
2019-05-27T15:28:18+08:00	26.006714	62	76.860001	5
2019-05-27T15:28:19+08:00	26.022736	62	77.720001	5
2019-05-27T15:28:25+08:00	26.121536	63	78.540001	5
2019-05-27T15:28:47+08:00	26.404594	60	97.439995	5
2019-05-27T15:28:51+08:00				
2019-05-27T15:29:47+08:00	26.615547	58	78.939995	
2019-05-27T15:30:47+08:00	26.658272	58	86.559998	
2019-05-27T15:31:47+08:00	26.700996	57	96.839996	
2019-05-27T15:32:47+08:00	26.700996	57	84.479996	
2019-05-27T15:33:47+08:00	26.743721	57	83.279999	



Data Report-GMM Showroom Freezer 1[CHANNEL ID:59278]

File Created: 31/05/2023 18:57:52

Sensor	Maximum	Minimum	Average
WiFi RSSI(dBm)	-23.00	-43.00	-28.11
External Temperature Probe(°C)	7.81	-25.31	-19.02

Data Report

Channel Name: GMM Showroom Freezer 1
 Data Start: 01/05/2023 00:00:00 to 30/05/2023 00:00:00
 Report Generated: 31/05/2023 18:57:59


The current data transmission has been truncated, there are 8000 pieces of data in total.
 Timezone: Asia/Singapore

Device Information

Channel Name: GMM Showroom Freezer 1
 Channel ID: 59278
 Serial: DR294W5L1
 Product ID: ubibot-ws1

Permission: Public
 Plan ID: ubibot_free
 Storage Used: 16.99 MB
 Download Traffic: 583.97 kB

Activated at: 10/02/2023 15:19:55
 Last Entry: 31/05/2023 18:54:49
 Firmware: v3.0.1
 WiFi SSID: GMMTechnoworld



Sensor	Maximum	Minimum	Average
Temperature(°C)	32.82	22.52	28.65
Humidity(%)	68.00	45.00	57.81
Light(lux)	366.24	0.08	101.81
Voltage(V)	5.00	5.00	5.00

1 of 192

2 of 192

Entry	Created At	Temperature	Entry	Created At	Temperature
1	01/05/2023 00:01:56	30.45	44	01/05/2023 03:38:59	30.58
2	01/05/2023 00:08:55	30.59	45	01/05/2023 03:43:59	30.52
3	01/05/2023 00:13:55	30.56	46	01/05/2023 03:48:59	30.50
4	01/05/2023 00:18:56	30.53	47	01/05/2023 03:53:59	30.55
5	01/05/2023 00:23:56	30.59	48	01/05/2023 03:58:59	30.53
6	01/05/2023 00:28:56	30.50	49	01/05/2023 04:03:59	30.53
7	01/05/2023 00:33:56	30.46	50	01/05/2023 04:08:59	30.69
8	01/05/2023 00:38:56	30.55	51	01/05/2023 04:13:59	30.65
9	01/05/2023 00:43:56	30.50	52	01/05/2023 04:18:59	30.66
10	01/05/2023 00:48:56	30.50	53	01/05/2023 04:23:59	30.73
11	01/05/2023 00:53:56	30.62	54	01/05/2023 04:28:59	30.73
12	01/05/2023 00:58:56	30.59	55	01/05/2023 04:33:59	30.71
13	01/05/2023 01:03:56	30.53	56	01/05/2023 04:38:59	30.60
14	01/05/2023 01:08:56	30.59	57	01/05/2023 04:43:59	30.73
15	01/05/2023 01:13:56	30.45	58	01/05/2023 04:48:59	30.74
16	01/05/2023 01:18:56	30.45	59	01/05/2023 04:53:59	30.84
17	01/05/2023 01:23:57	30.57	60	01/05/2023 04:58:59	30.76
18	01/05/2023 01:28:57	30.50	61	01/05/2023 05:03:59	30.74
19	01/05/2023 01:33:57	30.49	62	01/05/2023 05:08:59	30.81
20	01/05/2023 01:38:57	30.59	63	01/05/2023 05:13:59	30.77
21	01/05/2023 01:43:57	30.49	64	01/05/2023 05:18:59	30.77
22	01/05/2023 01:48:57	30.46	65	01/05/2023 05:23:59	30.89
23	01/05/2023 01:53:57	30.53	66	01/05/2023 05:28:59	30.74
24	01/05/2023 01:58:57	30.48	67	01/05/2023 05:33:59	30.76
25	01/05/2023 02:03:57	30.43	68	01/05/2023 05:38:59	30.77
26	01/05/2023 02:08:57	30.56	69	01/05/2023 05:44:00	30.73
27	01/05/2023 02:13:57	30.53	70	01/05/2023 05:49:00	30.70
28	01/05/2023 02:18:57	30.59	71	01/05/2023 05:54:00	30.86
29	01/05/2023 02:23:58	30.56	72	01/05/2023 05:59:00	30.73
30	01/05/2023 02:28:58	30.50	73	01/05/2023 06:04:00	30.65
31	01/05/2023 02:33:58	30.45	74	01/05/2023 06:09:00	30.73
32	01/05/2023 02:38:58	30.55	75	01/05/2023 06:14:00	30.67
33	01/05/2023 02:43:58	30.50	76	01/05/2023 06:19:00	30.67
34	01/05/2023 02:48:58	30.52	77	01/05/2023 06:24:00	30.77
35	01/05/2023 02:53:58	30.63	78	01/05/2023 06:29:00	30.73
36	01/05/2023 02:58:58	30.55	79	01/05/2023 06:34:00	30.67
37	01/05/2023 03:03:58	30.47	80	01/05/2023 06:39:00	30.74
38	01/05/2023 03:08:58	30.55	81	01/05/2023 06:44:00	30.65
39	01/05/2023 03:13:58	30.49	82	01/05/2023 06:49:00	30.65
40	01/05/2023 03:18:58	30.50	83	01/05/2023 06:54:00	30.63
41	01/05/2023 03:23:59	30.60	84	01/05/2023 06:59:00	30.73
42	01/05/2023 03:28:59	30.56	85	01/05/2023 07:04:00	30.70
43	01/05/2023 03:33:59	30.50	86	01/05/2023 07:09:00	30.77

6 of 192