

CEM DT-8820 4-in-1 digital Multifunction Environment Meter



SKU: CEMDT8820GY
Manufacture warranty period: 12 months

Description:

This popular handheld environment test meter is simple to operate has a large display and a few simple buttons to select the environment parameter to be measured. The 4 in 1 Environment test meter has a data hold and max hold switch plus a low battery indication and it auto powers off to save batteries. The environment light sensor is on a coiled cable to enable the light level measurements to be made without the operator shading the light reading sensor. The plug in K type thermocouple enables this environment meter to measure temperature in degrees Celsius or Fahrenheit. This 4 in 1 Environment testing meter also has a 4mm camera bush for tripod mounting. Save money on buying individual testing instruments with this incredibly cheap 4 in 1 Environmental Meter.

Features:

- The environment meter with 4 functions measure Sound level, Light, Humidity and Temperature
- 3 1/2 large LCD display with units of Lux, °C, %RH and C & dB, A & dB indication.
- Easy to use
- Environment Light measuring levers ranging from 0.01 lux to 20,000 lux.
- Environment Sound level range
A LO (low) – Weighting: 35-100 dB
A HI (High)- Weighting: 65-130 dB
C LO (low) – Weighting: 35-100 dB
C HI (High)- Weighting: 65-130 dB
Resolution: 0.1 dB
- Environment Humidity measurement from 25%RH to 95%RH with 0.1%RH resolution and fast time response.
- Environment Temperature measuring levers ranging from – 20.0°C ~ + 750°C / -4°F ~ + 1400°F



Specifications:

- **Temperature**
 - Range: -20°C~200°C
 - Resolution: 0.1°C
 - Accuracy (%rdg+digits): $\pm(3.0\%+2^{\circ}\text{C})$
 - Range: -20°C~750°C
 - Resolution: 1°C
 - Accuracy(%rdg+digits): $\pm(3.0\%+2^{\circ}\text{C})$
 $\leq 150^{\circ}\text{C}$; $\pm 3.0\% \geq 150^{\circ}\text{C}$
 - Range: -4°F~200°F
 - Resolution: 0.1°F
 - Accuracy (%rdg+digits): $\pm(3.0\%+2^{\circ}\text{F})$
 - Range: -4°F~1400°F
 - Resolution: 1°F
 - Accuracy(%rdg+digits): $\pm(3.0\%+2^{\circ}\text{F})$
 $\leq 302^{\circ}\text{F}$; $\pm 3.0\% \geq 302^{\circ}\text{F}$
- **Light**
 - Range: 20, 200, 2000, 20000 (2000 x 10 Lux)
 - Resolution: 0.01, 0.1, 1
 - Accuracy: $\pm(5.0\%+10\text{d})$
- **Humidity**
 - Range: 35%~95%RH
 - Resolution: 0.1%RH
 - Accuracy: $\pm 5.0\%$ RH at 25°C
- **Sound Level**
 - Range: 35dB~100dB
 - Resolution: 0.1dB
 - Accuracy: $\pm 3.5\text{dB}$ at 94dB sound level, 1KHz sine wave
- Size (H x W x D): 251mm x 63.8mm x 40mm
- Weight: 250g

Standard Certification:

- CE
- EMC
- EN: 61326

Package includes:

- Environment Meter with Sound probe
- 9V Batteries x 1
- User manual x 1
- K-type temperature probe x 1
- Humidity probe x 1
- Light probe x 1
- Gift box with carrying case

